

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20130624-R1431  
**Report Reference** R1431  
**Issue Date** 2013-June-24

**Issued to:** GLOBE TECHNOLOGIES CORP.  
1109 W Cedar St  
PO Box 1070  
Standish, MI 48658


**This is to certify that representative samples of** Fusible Links

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.


**Standard(s) for Safety:** ANSI/UL 33, "Heat Responsive Links for Fire-Protection Service."

**Additional Information:** See the UL Online Certifications Directory at [www.ul.com/database](http://www.ul.com/database) for additional information

Only those products bearing the UL Listing Mark should be considered as being covered by UL's Listing and Follow-Up Service.

The UL Listing Mark generally includes the following elements: the symbol UL in a circle:  with the word "LISTED"; a control number (may be alphanumeric) assigned by UL; and the product category name (product identifier) as indicated in the appropriate UL Directory.

Look for the UL Listing Mark on the product.



William R. Carney, Director, North American Certification Programs  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at [www.ul.com/contactus](http://www.ul.com/contactus)



# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20130624-R1431  
**Report Reference** R1431  
**Issue Date** 2013-June-24

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Issue B, in the 135, 165, 212, 280, 360 F temperature ratings; rated for loads 3-20 lbs incl.

Issue D, in the 165, 200 F temperature ratings; rated for loads 1-8 lbs incl.

Issue ML, in the 135, 165, 212, 280, 360, 450, 500 F temperature ratings; rated for loads from 10-40 lbs incl.

Model A, in the 135, 165, 212, 280, 360F, temperature ratings rated for loads 3-45 lbs incl.

Model A, in the 450 F temperature rating, rated for loads of 10-45 lbs. inclusive.

Model CS, in the 135 F temperature rating for loads of 1-4 lbs. incl.

Model EA, in the 135, 155, 165 and 212 °F temperature ratings; rated for loads 5-25 lbs. incl.

Model G, in the 155, 165, 212, 280, 350 F temperature ratings rated for loads 3-45 lbs incl.


Model GS, in the 155, 165, 212, 280, 350 F temperature ratings rated for loads 3-45 lbs incl.

Model J, in the 135, 155, 165, 212, 280 F temperature ratings; rated for loads of 3 to 10 lbs incl.

Model JE, in the 135, 155, 165, 212, 280 F temperature ratings, rated for loads of 3 to 10 lbs incl.

Model JS, in the 135, 155, 165, 212, 280 F temperature ratings, rated for loads of 3 to 10 lbs incl.

Model K, in the 135, 165, 212, 280, 360, 450 F temperature ratings; rated for loads 3-50 lbs. incl.



William R. Carney, Director, North American Certification Programs  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at [www.ul.com/contactus](http://www.ul.com/contactus)

